

SPECIFICATIONS

Customer Service: 1-800-460-7019
www.fluidfaucets.com

Specifications

- Heavy brass forged body construction for durability
- Pressure balancing with built-in 2-way diverter ceramic cartridge ensures anti-scald operation with life-long trouble-free service
- Built-in anti-back flow devices prevent cross flow.
- Single lever handle operation allows flow diversion and temperature control
- Integral stop valves for easy maintenance
- Three inlet connection option: 1/2" CxC soldering & 1/2" NPT thread or PEX or PEX-W
- Adjustable installation depth from 2-3/8"(60mm) to 3-1/8" (80mm)
- Enables back-to-back installation
- Bubble level is provided for easy and accurate installation.
- Mud guard is provided to protect trim finish.
- A wide selection of complimenting trims are sold separately

Flow Rate

- 4.5 gpm @ 60 psig

Finish

- Brass

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- IAPMO / cUPC Listed

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

fluid Pressure Balancing Valve with Built-in 2 Way Diverter Model: F1002B F1002B-PEX F1002B-PEX-W

