fluid Innovative fixtures for life

Specifications

- Metal construction for durability and reliability
- Pressure balancing volume control with 3 w-y diverter with shut off or sharing
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- 3 function round hand shower and slide rail w/ wall outlet
- 8" Square brass rain shower head and 16" shower arm
- Quad tub spout with fluid speed connection
- Requires pressure balancing valve with shut off F1003B or F1003B-PEX or F1003B-PEX-W OR pressure balancing valve with sharing F1003B-SHARE or F1003B-SHARE-PEX or F1003B-SHARE-PEX-W
- Valve and trim packages are sold separately

Finish

- CP (Polished Chrome)
- BN (PVD Brushed Nickel)

Flow Rate

- Shower head and hand shower 1.8 gpm @ 60 psig
- Tub spout 4.5 gpm @ 60 psig

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- IAPMO / cUPC Listed

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.


fluid Quad Series Shower Head, Hand Shower and Tub Spout Trim Kit Model: F163024T


Includes: F1001T FP801013 FP6001143-3PB FP605752 FP6016041 FA803 FP40120 FP6001006 FP6016034 FP6007108 FP6001050

Sleeve Tube and Cap Diverter Sleeve Tube Square Cover Plate Square Diverter Handle Quad Handle Slide Rail with Wall Outlet Round Hand Shower 60" Shower Hose Quad Tub Spout 16" Shower Arm 8" Square Shower Head











Sustainable Solutions 8395 Riverbend Court, Burnaby, BC V3N 5E7, Canada

F163024T / REV0 2021

Sustainable Solutions