SPECIFICATIONS

Customer Service: 1-800-460-7019 www.fluidfaucets.com

Specifications

- Metal construction for durability and reliability
- Pressure balancing volume control with 3-way diverter with shut off or sharing
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- 3 function round hand shower and slide rail w/ wall outlet
- 8" Square brass rain shower head and 16" shower arm
- Oceanside tub spout with fluid speed connection
- Requires pressure balancing valve with shut off F1003B or F1003B-PEX or F1003B-PEX-W OR
- pressure balancing valve with sharing F1003B-SHARE or F1003B-SHARE-PEX or F1003B-SHARE-PEX-W
- Valve and trim packages are sold separately

Finish

- CP (Polished Chrome)
- BN (PVD Brushed Nickel)

Flow Rate

- Shower Head and Hand Shower 1.8 gpm @ 60 psig
- Tub Spout 4.5 gpm @ 60 psig

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- IAPMO / cUPC Listed

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

1 6" [406.3mm]

2³/₈" -3³/₁₆" 6" [152.2mm]

5-(1/2"-14NPT)

fluid Oceanside/Vancouver Series **Shower Head, Hand Shower** and Tub Spout Trim Kit Model: F233024T

Includes:

F1001T FP6001143-3PB FP801013 FP605752 FP6023041 FA803 FP40120 FP6001006 FP6023034 FP6007108 FP6001050

Sleeve Tube and Cap Square Cover Plate Diverter Sleeve Tube Square Diverter Handle Oceanside/Vancouver Handle Slide Rail with Wall Outlet 3 Function Hand Shower 60" Shower Hose Oceanside Tub Spout 16" Shower Arm 8" Square Shower Head





