

## **TOLMIN**

#### **Features**

- Solid brass construction
- · Brass valve bodies
- Quarter-turn washerless ceramic disc valve cartridges
- Spout assembly with integral supply hoses
- Push Pop-Up drain with tailpiece
- 5.94" (15.1 cm) spout height at outlet
- 7.13" (18.1 cm) spout reach (c-c)
- For 8" (20.3 cm) centers Maximum 20" (50.8 cm)
- ADA Compliant
- 1.2 GPM (4.5 LPM) Max

#### **Codes / Standards Compliance**

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1
- IAMPO/cUPC
- NSF/ANSI/CAN 61, SECTION 9
- NSF/ANSI 372
- IPC
- ADA & ICC/ANSI A117.1
- Energy Policy Act of 1992
- EPA WaterSense
- California Energy Commission
- All applicable US Federal and State material regulations

#### **Colors / Finishes**

- 10B: Oil Rubbed Bronze15: Polished Nickel
- 15S: Satin Nickel PVD
- 26: Polished Chrome
- Other: Refer to the Newport Brass catalog for additional color/finish options.

## **Widespread Lavatory Faucet**

3330C









# Specified Model Model Description Colors | Finishes 3330C Widespread Lavatory Faucet 10B 15 15S 26 Other

### Product Specification Add "Color / Finish" suffix to Model number, below.

The two-handle Widespread Lavatory Faucet shall be made of solid brass construction. Faucet shall incorporate a spout assembly with integral supply hoses and feature brass valve bodies with quarter-turn washerless ceramic disc valve cartridges. Faucet shall have a 1.2 gallon (4.5 liter) per minute maximum flow rate. Product shall be for 8" (20.3 cm) centers - Maximum 20" (50.8 cm). Product shall incorporate a 5.94" (15.1 cm) spout height at outlet and a 7.13" (18.1 cm) spout reach (c-c). Faucet shall include a pop-up drain with tailpiece and incorporate cross handles. Widespread Lavatory Faucet shall be Newport Brass Model 3330C/\_\_\_\_\_.

# 3330C

#### **PRODUCT DIMENSIONS** (Units are in inches)

Product Dimensions are provided for reference only. For specific product installation guidelines, please reference the Installation Instructions of the product being installed.

