Ideal BarTap® with Filtration

High Flow (HF) or Eco Flow (EF)





IBTF-D-BSS-HF IBTF-D-BSS-EF

PVD Satin Black

IBTF-D-YSS-HF IBTF-D-YSS-EF IBTF-D-RSS-HF IBTF-D-RSS-EF



Specifications

Ideal BarTap

Single-lever control

Ceramic disk cartridge

Forward rotating COMFORTFEEL™ lever handle

Q-Dock™ docking system holds hand spray in place

Ergonomic slide switch to select Ideal Flow, Laminar or Spray Flow

Automatic return to laminar flow

Concealed easy clean spray face

Spout rotates 360°

Counterweight

Dual check valves

24" stainless steel flexible hoses 3/8" compression

Maximum counter thickness 2"

Minimum install hole diameter 1 3/8" Optional base ring included

Total height 15 13/16"

High Flow 2.2 GPM* maximum flow rate

Eco Flow 1.8 GPM* maximum flow rate

For use with Water Filtration System (included)

*Note: May reduce water flow



Water Filtration System (Included)

Water Filtration System

Service flow rate 2.0 gpm

Rated capacity 7,900 gallons

Operating pressure 10 - 125 psi Operating temperature 35 - 100°F

Overall dimensions 16 7/8" x 4 1/8"

Reduces lead, chlorine, cysts and other contaminants

Quick twist-lock cartridge replacement

Replacement filter cartridge dimensions 14 1/2" x 3"

Internal parts never exposed to human handling Filtration protects capital equipment from early breakdown

Installs vertically (allow 2 1/2" clearance)

Parts Included: Mounting bracket and screws, plastic tubing, push-fit Tee

Construction

PVD Gun Metal Gray Stainless Steel

Ideal BarTap

Solid 316L machined stainless steel construction Available in Polished, Matte, PVD Gun Metal Grav™, PVD Satin Black, PVD Brushed Gold, PVD Polished Rose Gold Indoor & outdoor

Limited Lifetime Warranty

Made in Italy

Water Filtration System

Five Year Warranty Made in the USA

Codes/Standards

Ideal BarTap

ASME 112.18.1 CSA B125.1

NSF 61, 372

CALGreen

UPC

NPC ADA

Water Filtration System

IAPMO Certified

NSF/ANSI 42, 53, 372

